

ELECTROCHEMICAL CELLS USING AGAR MEDIA

PURPOSE



This is an Investigation of Oxidation-Reduction Reactions through the chemistry of an electrochemical cell.

INTRODUCTION

Electrochemical cells are familiar - a flashlight operates on current drawn from electrochemical cells called dry cells, and automobiles are started with the aid of a battery, a set of electrochemical cells in tandem. The last time you changed the dry cells in a flashlight because the old ones were “dead”, did you wonder what happened inside those cells? Why does electric current flow from a new dry cell but not from one that has been used many hours? We shall see that this is an important question in chemistry. By studying the chemical reactions that occur in an electrochemical cell we discover a basis for predicating whether equilibrium in a reaction favors reactants or products.

There are several interesting features about these half reactions:

- 1) The two half-reactions are written separately.
- 2) Electrons are shown as part of the reaction.
- 3) New chemical species are produced in each half reaction.
- 4) The half-reactions, when combined, express the overall, or net, reaction.
- 5) The half-reaction in which electrons are lost is called **oxidation**.
- 6) The half-reaction in which electrons are gained is called **reduction**.
- 7) The overall reaction is called an **oxidation-reduction reaction**.



LEO the lion goes **GER**

Leo = loss of electron – oxidation **Ger** = gain of electrons - reduction

PROCEDURE

1. Add three drops of 0.1 M NaCl to a strip of paper and place it so that a bridge is formed between the surfaces of two of the individual cells.
2. Insert a copper strip into the CuSO₄ /agar media. By selecting two half cells to be coupled together in this manner an electrochemical cell that is a galvanic or voltaic cell is formed. Other cell arrangements can be made using the NiSO₄/agar media and the MgSO₄/agar media.
3. Set up the Lab Pro to read voltage. Connect the voltage probe to the cell and measure the cell potential. The zinc electrode is cathodic and the copper electrode is anodic.
4. Put together the cell combinations indicated on the data sheet, measure the experimental potentials (volts), and determine the cell efficiency for each arrangement.

GIVEN:

$$E_0 = (E_1^0) - (E_2^0)$$

OXIDIZED STATE		REDUCED STATE	E ⁰ (volts)
Mg ⁺⁺ + 2e	↔	Mg ⁰	+2.37
Zn ⁺⁺ + 2e	↔	Zn ⁰	+0.76
Ni ⁺⁺ + 2e	↔	Ni ⁰	+0.25
Cu ⁺⁺ + 2e	↔	Cu ⁰	-0.34

STUDENT DATA SHEET

Name (s):

Date:

Cell Operation and Efficiency Determinations:

Cell	Measured Potential (volts)	Calculated Potential (volts)	Cell Efficiency (%)*
copper/zinc			
copper/nickel			
copper/magnesium			
nickel/magnesium			
nickel/zinc			

$$\text{*Cell efficiency (\%)} = \frac{\text{experimental voltage}}{\text{Calculated voltage}} \times 100$$

DISCUSSION

1. Sketch and label the arrangement of the cell parts as the cell is ready for operation.

2. It is possible that your experimental cell voltage is not the same as the theoretical or accepted value. Discuss at least two reasons for this occurrence.

3. Discuss how and why the electrons move in these cells.

4. How would you change the arrangement of the cell to make it a electrolytic cell?

References

Gel Cels, Instructor's Manual by T& S Educational, Inc.
Cells, Gels and the Enzymes of Life, F. H. Pallock, May 2001
Biochemistry, Cell & Molecular Biology, J. Rudman, 1999
A Beginners Guide to Blood Cells, B.J. Bain, 1996